

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2025

Print date: 16 Feb 2026

Version: 2.1

detax

Page 1/12

Dip coat

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Dip coat

UFI:

01KC-YPXQ-T34W-62Q6

1.2. Relevant identified uses of the substance or mixture and uses advised against

No data available

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

detax GmbH

Carl-Zeiss-Str. 4

76256 Ettlingen

Germany

Telephone: +49 7243 510 0

E-mail: post@detax.com

Website: www.detax.com

1.4. Emergency telephone number

24h: +1-800-424-9300 (CHEMTREC worldwide)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	On basis of test data.
Aspiration hazard (<i>Asp. Tox. 1</i>)	H304: May be fatal if swallowed and enters airways.	Calculation method.
Acute toxicity (dermal) (<i>Acute Tox. 4</i>)	H312: Harmful in contact with skin.	Calculation method.
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	Calculation method.
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	Calculation method.
Acute toxicity (inhalative) (<i>Acute Tox. 4</i>)	H332: Harmful if inhaled.	Calculation method.
STOT-repeated exposure (<i>STOT RE 2</i>)	H373: May cause damage to organs through prolonged or repeated exposure.	Calculation method.
Hazardous to the aquatic environment (<i>Aquatic Acute 1</i>)	H400: Very toxic to aquatic life.	Calculation method.
Hazardous to the aquatic environment (<i>Aquatic Chronic 1</i>)	H410: Very toxic to aquatic life with long lasting effects.	Calculation method.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2025

Print date: 16 Feb 2026

Version: 2.1

detax

Page 2/12

Dip coat

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS07
Exclamation mark



GHS08
Health hazard



GHS09
Environment

Signal word: Danger

Hazard components for labelling:

xylene; Silanamin, 1,1,1-Trimethyl-N-(trimethylsilyl)-, Hydrolyseprodukte mit Siliciumdioxid; dioctyltin di(acetate); MTA - Methyltriacetoxysilan

Hazard statements for physical hazards

H225	Highly flammable liquid and vapour.
------	-------------------------------------

Hazard statements for health hazards

H304	May be fatal if swallowed and enters airways.
H312 + H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Hazard statements for environmental hazards

H410	Very toxic to aquatic life with long lasting effects.
------	---

Supplemental hazard information: none

Precautionary statements Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/....

Precautionary statements Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/....
P370 + P378	In case of fire: Use ... to extinguish.

Special rules for supplemental label elements for certain mixtures:

21,4 % percent of the mixture consists of ingredient(s) of unknown acute toxicity (oral).
81,7 % percent of the mixture consists of ingredient(s) of unknown acute toxicity (dermal).
81,7 % percent of the mixture consists of ingredient(s) of unknown acute toxicity (inhalative).

2.3. Other hazards

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2025

Print date: 16 Feb 2026

Version: 2.1

detax

Page 3/12

Dip coat

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 108-87-2 EC No.: 203-624-3 Index No.: 601-018-00-7 REACH No.: 01-2119556887-18-XXXX	methylcyclohexane Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), Skin Irrit. 2 (H315)  Danger Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg	20 - < 50 weight-%
CAS No.: 1330-20-7 EC No.: 215-535-7 Index No.: 601-022-00-9 REACH No.: 01-2119488216-32	xylene Acute Tox. 4 (H332, H312), Aquatic Chronic 3 (H412), Asp. Tox. 1 (H304), Eye Irrit. 2 (H319), Flam. Liq. 3 (H226), STOT RE 2 (H373), STOT SE 3 (H335), Skin Irrit. 2 (H315)  Danger Acute Toxicity Estimate ATE (dermal) 1,100 mg/kg ATE (inhalation, vapour) 11 mg/L ATE (inhalation, dust/mist) 1.5 mg/L	10 - < 20 weight-%
CAS No.: 68909-20-6 EC No.: 272-697-1 Index No.: 014-052-00-7 REACH No.: 01-2119962266-32	Silanamin, 1,1,1-Trimethyl-N-(trimethylsilyl)-, Hydrolyseprodukte mit Siliciumdioxid STOT RE 2 (H373)  Warning EUH066 Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg	5 - < 20 weight-%
CAS No.: 4253-34-3 EC No.: 224-221-9	MTA - Methyltriacetoxysilan Skin Corr. 1B (H314)  Danger	0 - ≤ 5 weight-%
CAS No.: 17586-94-6 EC No.: 241-555-0	dioctyltin di(acetate) Acute Tox. 2 (H330), Eye Dam. 1 (H318), STOT SE 2 (H371), Skin Corr. 1A (H314)  Danger Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg ATE (inhalation, vapour) 0.43 mg/L	0 - ≤ 1 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended. Warning First aider: Pay attention to self-protection!

Following inhalation:

Provide fresh air. In case of respiratory tract irritation, consult a physician. Get medical advice/attention. Get medical advice/attention if you feel unwell.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention.

After eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2025

Print date: 16 Feb 2026

Version: 2.1

detax

Page 4/12

Dip coat

Following ingestion:

Rinse mouth. Let 1 glass of water be drunken in little sips (dilution effect). Get medical advice/attention if you feel unwell. Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Get immediate medical advice/attention.

Self-protection of the first aider:

Use personal protection equipment. Avoid contact with skin, eyes and clothes. No direct artificial respiration to be given by first aider.

4.2. Most important symptoms and effects, both acute and delayed

Pneumonia Pulmonary oedema Skin corrosion/irritation Serious eye damage/eye irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water spray jet alcohol resistant foam Extinguishing powder Carbon dioxide (CO₂)

5.2. Special hazards arising from the substance or mixture

Combustible

Hazardous combustion products:

In case of fire: Gases/vapours, toxic

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Remove persons to safety.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

6.5. Additional information

Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Wear personal protection equipment (refer to section 8).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2025

Print date: 16 Feb 2026

Version: 2.1

detax

Page 5/12

Dip coat

Fire prevent measures:

Keep away from sources of ignition - No smoking.

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Storage class (TRGS 510, Germany): 3 – Flammable liquids

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
TRGS 900 (DE)	methylcyclohexane CAS No.: 108-87-2 EC No.: 203-624-3	① 200 ppm (810 mg/m ³) ② 400 ppm (1,620 mg/m ³) ⑤ DFG
IOELV (EU)	xylene CAS No.: 1330-20-7 EC No.: 215-535-7	① 50 ppm (221 mg/m ³) ② 100 ppm (442 mg/m ³) ⑤ (may be absorbed through the skin)
TRGS 900 (DE) from 2 Oct 2020	xylene CAS No.: 1330-20-7 EC No.: 215-535-7	① 50 ppm (220 mg/m ³) ② 100 ppm (440 mg/m ³) ⑤ (kann über die Haut aufgenommen werden) DFG, EU, H
TRGS 900 (DE) from 23 Jun 2022	dioctyltin di(acetate) CAS No.: 17586-94-6 EC No.: 241-555-0	① 0.002 ppm (0.01 mg/m ³) ② 0.004 ppm (0.02 mg/m ³) ⑤ (n-Octylzinnverbindungen) H, Y, 10, 11, AGS, DFG

8.1.2. Biological limit values

Limit value type (country of origin)	Substance name	Limit value	① Parameter ② Test material ③ Time of sampling: ④ Remark
TRGS 903 (DE) from 1 Nov 2016	xylene CAS No.: 1330-20-7 EC No.: 215-535-7	2,000 mg/L	① Methylhippur-(Tolur-)säure (alle Isomere) ② Urin ③ Expositionsende bzw. Schichtende
BAT (DE) from 1 Jul 2024	xylene CAS No.: 1330-20-7 EC No.: 215-535-7	1,800 g	① Methylhippur-(Tolur-)säure (alle Isomere) ② Urin ③ Expositionsende bzw. Schichtende

8.1.3. DNEL-/PNEC-values

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2025

Print date: 16 Feb 2026

Version: 2.1

detax

Page 6/12

Dip coat

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No data available

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection EN 166

Skin protection:

Tested protective gloves must be worn EN ISO 374 Suitable material: Breakthrough time: min In the case of wanting to use the gloves again, clean them before taking off and air them well. Breakthrough times and swelling properties of the material must be taken into consideration.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Form: Liquid

Colour: colourless

Odour: not determined

flammability: Yes

Safety relevant basis data

Parameter	Value	① Method ② Remark
pH	No data available	
Melting point	No data available	
Freezing point	No data available	
Initial boiling point and boiling range	> 100 °C	
Flash point	= -4 °C	
Evaporation rate	No data available	
Auto-ignition temperature	No data available	
Upper/lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Density	No data available	
Bulk density	not applicable	
Water solubility	No data available	
Dynamic viscosity	No data available	
Kinematic viscosity	No data available	

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2025

Print date: 16 Feb 2026

Version: 2.1

detax

Page 7/12

Dip coat

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

Gases/vapours, toxic

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information

Acute Toxicity Estimate for Mixtures

ATE (dermal): 1,110.8 mg/kg

methylcyclohexane CAS No.: 108-87-2 EC No.: 203-624-3

LD₅₀ oral: >2,000 mg/kg (Kaninchen)

Silanamin, 1,1,1-Trimethyl-N-(trimethylsilyl)-, Hydrolyseprodukte mit Siliciumdioxid CAS No.: 68909-20-6
EC No.: 272-697-1

ATE oral: ≥1,000 mg/kg

LD₅₀ oral: >2,000 mg/kg (Rat) OECD Prüfrichtlinie 401

MTA - Methyltriacetoxysilan CAS No.: 4253-34-3 EC No.: 224-221-9

ATE oral: 73.4 mg/kg

dioctyltin di(acetate) CAS No.: 17586-94-6 EC No.: 241-555-0

LD₅₀ oral: >2,000 mg/kg (Ratte)

LC₅₀ Acute inhalation toxicity (vapour): 0.43 mg/L 4 h (Maus)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Harmful in contact with skin.

Acute inhalation toxicity:

Harmful if inhaled.

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard:

May be fatal if swallowed and enters airways.

Additional information:

No data available

11.2. Information on other hazards

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2025

Print date: 16 Feb 2026

Version: 2.1

detax

Page 8/12

Dip coat

SECTION 12: Ecological information

12.1. Toxicity

methylcyclohexane CAS No.: 108-87-2 EC No.: 203-624-3

LC₅₀: 2.07 mg/L 4 d (fish, *Oryzias latipes*) OECD Prüfrichtlinie 203

EC₅₀: 0.326 mg/L 2 d (crustaceans, *Daphnia magna*) OECD- Prüfrichtlinie 202

NOEC: 0.022 mg/L 3 d (*Pseudokirchneriella subcapitata*) OECD-Prüfrichtlinie 201

ErC₅₀: 0.134 mg/L 3 d (Algae/water plant, *Pseudokirchneriella subcapitata*) OECD-Prüfrichtlinie 201

NOEC: 0.022 mg/L 3 d (*Pseudokirchneriella subcapitata*) OECD-Prüfrichtlinie 201

ErC₅₀: 0.134 mg/L 3 d (Algae/water plant, *Pseudokirchneriella subcapitata*) OECD-Prüfrichtlinie 201

xylene CAS No.: 1330-20-7 EC No.: 215-535-7

LC₅₀: =780 mg/L 4 d (fish, *Cyprinus carpio* (Wasserfloh))

LC₅₀: =0.6 mg/L 2 d (Algae/water plant)

LC₅₀: 23.53 - 29.97 mg/L 4 d (*Pimephales promelas*)

LC₅₀: >780 mg/L 4 d (*Cyprinus carpio*)

LC₅₀: 30.26 - 40.75 mg/L 4 d (*Poecilia reticulata*)

LC₅₀: 7,711 - 9,591 mg/L 4 d (*Lepomis macrochirus*)

LC₅₀: =19 mg/L 4 d (*Lepomis macrochirus*)

LC₅₀: 13.1 - 16.5 mg/L 4 d (*Lepomis macrochirus*)

LC₅₀: 13.5 - 17.3 mg/L 4 d (*Oncorhynchus mykiss*)

LC₅₀: 2,661 - 4,093 mg/L 4 d (*Oncorhynchus mykiss*)

LC₅₀: =13.4 mg/L 4 d (*Pimephales promelas*)

EC₅₀: =3.82 mg/L 2 d

EC₅₀: =0.0084 mg/L 1 d

Silanamin, 1,1,1-Trimethyl-N-(trimethylsilyl)-, Hydrolyseprodukte mit Siliciumdioxid CAS No.: 68909-20-6
EC No.: 272-697-1

LC₅₀: >10,000 mg/L 4 d (*Brachydanio rerio*) OECD 203

EC₅₀: >173 mg/L 3 d (Algae/water plant, *Desmodesmus subspicatus* (Grünalge)) OECD 201

EC₅₀: >173 mg/L 3 d (Algae/water plant, *Desmodesmus subspicatus* (Grünalge)) OECD 201

LC₅₀: >10,000 mg/L 4 d (*Brachydanio rerio*) OECD 203

EC₅₀: >173 mg/L 3 d (Algae/water plant, *Desmodesmus subspicatus* (Grünalge)) OECD 201

MTA - Methyltriacetoxysilan CAS No.: 4253-34-3 EC No.: 224-221-9

LC₅₀: 96.59 mg/L 4 d (*Pimephales promelas*) OECD 203

EC₅₀: 21.65 mg/L 3 d (*Pseudokirchneriella subcapitata*) OECD 201

EC₅₀: 79.47 mg/L 2 d (*Daphnia magna*) OECD 202

NOEC: 15.97 mg/L 3 d (*Pseudokirchneriella subcapitata*) OECD 201

LC₅₀: 96.59 mg/L 4 d (*Pimephales promelas*) OECD 203

EC₅₀: 21.65 mg/L 3 d (*Pseudokirchneriella subcapitata*) OECD 201

NOEC: 15.97 mg/L 3 d (*Pseudokirchneriella subcapitata*) OECD 201

Aquatic toxicity:

Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

methylcyclohexane CAS No.: 108-87-2 EC No.: 203-624-3

Biodegradation: Poorly biodegradable.

12.3. Bioaccumulative potential

methylcyclohexane CAS No.: 108-87-2 EC No.: 203-624-3

Log K_{ow}: 3.88

Bioconcentration factor (BCF): 321

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2025

Print date: 16 Feb 2026

Version: 2.1

detax

Page 9/12

Dip coat

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

methylcyclohexane CAS No.: 108-87-2 EC No.: 203-624-3
Results of PBT and vPvB assessment: —
xylene CAS No.: 1330-20-7 EC No.: 215-535-7
Results of PBT and vPvB assessment: —
Silanamin, 1,1,1-Trimethyl-N-(trimethylsilyl)-, Hydrolyseprodukte mit Siliciumdioxid CAS No.: 68909-20-6 EC No.: 272-697-1
Results of PBT and vPvB assessment: —
MTA - Methyltriacetoxysilan CAS No.: 4253-34-3 EC No.: 224-221-9
Results of PBT and vPvB assessment: —
dioctyltin di(acetate) CAS No.: 17586-94-6 EC No.: 241-555-0
Results of PBT and vPvB assessment: —

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV
Directive 2008/98/EC (Waste Framework Directive)

HP 3	Flammable
HP 4	Irritant — skin irritation and eye damage
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 14	Ecotoxic

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1866	UN 1866	UN 1866	UN 1866
14.2. UN proper shipping name			
RESIN SOLUTION	RESIN SOLUTION	RESIN SOLUTION (octamethylcyclotetrasiloxane)	RESIN SOLUTION
14.3. Transport hazard class(es)			
 3	 3	 3	 3
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
		 MARINE POLLUTANT	No

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2025

Print date: 16 Feb 2026

Version: 2.1

detax

Page 10/12

Dip coat

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.6. Special precautions for user			
Special Provisions: 640D Limited quantity (LQ): 5 L Excepted Quantities (EQ): E2 Hazard identification number (Kemler No.): 33 Classification code: F1 Tunnel restriction code: (D/E)	Special Provisions: 640D Limited quantity (LQ): 5 L Excepted Quantities (EQ): E2 Classification code: F1	Special Provisions: - Limited quantity (LQ): 5 L Excepted Quantities (EQ): E2 EmS-No.: F-E, S-E	Special Provisions: A3 Limited quantity (LQ): Y341 Excepted Quantities (EQ): E2

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Other regulations (EU):

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive], Hazard categories:

- P5a Flammable Liquids, Category 1 or 2
- P5b Flammable liquids
- P5c Flammable liquids of Categories 2 or 3, not covered by P5a and P5b
- E1 Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1

15.1.2. National regulations

[DE] National regulations

Water hazard class

WGK:

2 - obviously hazardous to water

15.2. Chemical Safety Assessment

No data available

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DIN	German Institute for Standardization / German Industrial Standard
DNEL	derived no-effect level
EC ₅₀	Effective Concentration 50%
EN	European Standard
ES	Exposure scenario

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2025

Print date: 16 Feb 2026

Version: 2.1

detax

Page 11/12

Dip coat

EWC	European Waste Catalogue
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
ISO	International Standards Organisation
LC ₅₀	Lethal (fatal) Concentration 50%
LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	On basis of test data.
Aspiration hazard (<i>Asp. Tox. 1</i>)	H304: May be fatal if swallowed and enters airways.	Calculation method.
Acute toxicity (dermal) (<i>Acute Tox. 4</i>)	H312: Harmful in contact with skin.	Calculation method.
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	Calculation method.
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	Calculation method.
Acute toxicity (inhalative) (<i>Acute Tox. 4</i>)	H332: Harmful if inhaled.	Calculation method.
STOT-repeated exposure (<i>STOT RE 2</i>)	H373: May cause damage to organs through prolonged or repeated exposure.	Calculation method.
Hazardous to the aquatic environment (<i>Aquatic Acute 1</i>)	H400: Very toxic to aquatic life.	Calculation method.
Hazardous to the aquatic environment (<i>Aquatic Chronic 1</i>)	H410: Very toxic to aquatic life with long lasting effects.	Calculation method.

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Mar 2025
Print date: 16 Feb 2026
Version: 2.1



Page 12/12

Dip coat

Hazard statements	
H335	May cause respiratory irritation.
H371	May cause damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6. Training advice

No data available

16.7. Additional information

No data available