

Annex 1

Digital light Processing (DLP) printer, operation software and parameter

Model (Picture)	Printer Manufacturer	Light source	Light intensity	Operation Software	Parameter data set*
	Asiga Max	385 nm	6.1 mW/cm ²	Composer 1.2.11	Detax_Freeprint ortho 385_5
	Asiga Max 2	385 nm	7.0 mW/cm ²	Composer 2.0.8	Detax_Freeprint ortho 385_5
	Asiga Pico 2	385 nm	20 mW/cm ²	Composer 1.2.11	Detax_Freeprint ortho 385_5
	Asiga PRO 2	385 nm	5.7 mW/cm ²	Composer 1.2.11	Detax_Freeprint ortho 385_5
	Asia PRO 4K	385 nm	7.0 mW/cm ²	Composer 1.2.11	Detax_Freeprint ortho 385_5
	Asiga Ultra	385 nm	6.6 mW/cm ²	Composer 2.0.8	Detax_Freeprint ortho 385_5

*The set of parameters includes all relevant material- and printer specific information

Annex 1

Digital light Processing (DLP) printer, operation software and parameter

Model (Picture)	Printer Manufacturer	Light source	Light intensity	Operation Software	Parameter data set*
	Ivoclar PrograPrint PR5	388 nm	16 mW/cm ²	PrograPrint CAM 1.1.10.1	DetaxFREEPRINT ortho
	Microlay Versus	385 nm	4.3 mW/cm ²	Microform 1.0.3.7	DETAX Freeprint Ortho 385 100 microns v5.3
	Miicraft Alpha	385 nm	6.0 mW/cm ²	Utility 6.4.4	DETAX freeprint ortho
	Miicraft Prime Series	385 nm	6.2 mW/cm ²	Utility 6.3.0	Detax_Freeprint ortho 385_100_PH
	Miicraft Ultra Series	385 nm	5.7 mW/cm ²	Utility 6.3.0	Detax_Freeprint ortho UV_100
	Phrozen Sonic 4K 2022**	405 nm	2.0 mW/cm ²	Phrozen DS Slicer	DETAX Freeprint ortho 405

*The set of parameters includes all relevant material- and printer specific information

** The printers only works with the Freeprint ortho 405.

Annex 1

Digital light Processing (DLP) printer, operation software and parameter

Model (Picture)	Printer Manufacturer	Light source	Light intensity	Operation Software	Parameter data set*
	Rapidshape D10+ / D20+/ D30+ / D40+	385 nm	2.0 mW/cm ²	Netfabb 2020	DETAX Freeprint- ortho uv
	Rapidshape D70+ / D90+	385 nm	5.0 mW/cm ²	Netfabb 2020	DETAX Freeprint- ortho uv
	Way2Production SolFlex Series	385 nm	8.0 mW/cm ²	Netfabb 2020	Freeprint ortho 385

*The set of parameters includes all relevant material- and printer specific information

Cleaning Equipment

Cleaning unit

Manufacturer, Model	Cleaning process
---------------------	------------------

Ivoclar PrograPrint Clean	Clean the parts with isopropyl alcohol (purity $\geq 98\%$) for 3 minutes. Then thoroughly clean the openings, cavities and gap areas with compressed air. The main cleaning is performed in a separate vessel with fresh isopropyl alcohol (purity $\geq 98\%$) for 3 minutes. Prior to post-exposure, check the openings, cavities and gap areas for residues. Then blow off with compressed air.
--------------------------------------	--

Rapidshape RS Wash	Use the following settings: DETAX Freeprint-ortho uv Prior to post-exposure, check the openings, cavities and gap areas for residues. Then blow off with compressed air.
-------------------------------	---

Ultrasonic bath Bandelin Sonorex	Clean the parts with isopropyl alcohol (purity $\geq 98\%$) for 3 minutes. Then thoroughly clean the openings, cavities and gap areas with compressed air. The main cleaning is performed in a separate vessel with fresh isopropyl alcohol (purity $\geq 98\%$) for 3 minutes. Prior to post-exposure, check the openings, cavities and gap areas for residues. Then blow off with compressed air.
---	---



detax GmbH

Carl-Zeiss-Str. 4 • 76275 Ettlingen • Germany
+49 7243 510 0 • post@detax.com • detax.com

07/2025

Light curing Equipment

Light Curing unit Manufacturer, Model	Curing process
Ivoclar PrograPrint Cure	Post curing A: Wavelength = 405 nm; Intensity = 100 %; Duration = 120 s Post curing B: Wavelength = 460 nm; Intensity = 100 %; Duration = 120 s
NK Optik Otofash G171	2 x 2000 flashes under inert gas, turn around components after 2000 flashes
NK Optik Otofash 250/500	4000 flashes under inert gas @15 Hz
Rapidshape RS Cure	Use the following settings: DETAX Freeprint-ortho uv
Rapidshape RS cure XL	Use the following settings: DETAX Freeprint-ortho uv



detax GmbH

Carl-Zeiss-Str. 4 • 76275 Ettlingen • Germany
+49 7243 510 0 • post@detax.com • detax.com

07/2025